

As Refreshing As A...  *Sea Breeze*

Window Room Air Conditioners



High Efficiency, Quiet Operation and Stylish Compact Design

FEATURES:

- Multiple Functions - Cooling, Dehumidifying & Fan Ventilation
- 3 Speed Fan Selection - Low/Medium/High
- Electronic Touch Control Panel
- Digital Display
- Installation Kit with Expandable Side Panels
- Retracting Louvers
- Slide-Out, Washable Filter
- Window or Through-the-Wall Installation
- Slide Out Galvanized Steel Cabinet for Easy Installation
- Protective Rear Grille & Cabinet

Specifications listed on back



Supco - Sealed Unit Parts Co., Inc.
2200 Landmark Place
Allenwood, NJ 08720
Phone: 732-223-6644 Fax: 732-223-1617
www.supco.com -or- info@supco.com



WINDOW UNIT SPECIFICATIONS


PERFORMANCE DATA					
Unit #	WA12YR	WA18ZR	WA24ZR	WH12ZM	WH18ZM
BTU Cooling	12000	18000	24000	11200	18000
BTU Heating	na	na	na	10700	11000
SEER	9.8	9.7	8.5	9.8	9.7
Dehumidification (pints/hour)	2.7	4.6	6.5	2.6	4.2
Airflow (CFM)	294	459	618	310	450
Voltage	115	208/230	208/230	208/230	208/230
Frequency/cycle	60	60	60	60	60
AMPS Cooling	14.56	12.57	13.1	5.7	8.75
AMPS Heating	na	na	na	14.84	15.4
Watts Cooling	1210	1850	2740	1164	1885
Watts Heating	na	na	na	3500	3500
Plug Type	Type A	Type C	Type C	Type B	Type C
Power Cord Rating/amps	15	20	20	20	20
Power Cord Type	LCDI	LCDI	LCDI	LCD1	LCD1
Power Cord Length	6'	6'	6'	6'	6'
Refrigerant	R22	R22	R22	R22	R22
Refrigerant Charge/oz.	33.12	27.84	33.44	32.32	27.86
Sound (indoor/outdoor) dba	56/61	56/61	56/61	58/62	59/63
4 Way Air Adjustment	yes	yes	yes	yes	yes
2 Way Air Swing	yes	yes	yes	yes	yes
Air Discharge	Top	Side	Side	Top	Side
Motor Type	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing
Motor Capacitor	15uf	7uf	7uf	4uf	7uf

Unit #	WA12YR	WA18ZR	WA24ZR	WH12ZM	WH18ZM
Controls	Remote	Remote	Remote	Mechanical	Mechanical
Thermostat Temperature	64° to 86° F	64° to 86° F	64° to 86° F	64° to 86° F	64° to 86° F
Cabinet Size/inches					
Width	22.5	26	26	22.5	26
Depth	24	28	30.5	24	28
Height	15.5	17	17	15.5	17
Window Opening/inches	27-38	30-46	30-46	28-44	30-46
Thru-Wall Max Thickness	5.5	8.5	8.5	5.5	8.5
Weight/lbs	115/97	163/150	183/165	114/97	163/150
Approvals	UL/CUL	UL/CUL	UL/CUL	UL/CUL	UL/CUL

WINDOW INSTALLATION

Window Opening Measurements 1200 BTU


B=16 1/4" min.
opening height



A= 27" min. to 38" max opening width

Window Opening Measurements 1800 & 2400 BTU

B=20" min.
opening height



A= 30" min. to 40" max opening width

- A 125 VOLT 15 AMP**
- B 250 VOLT 15 AMP**
- C 250 VOLT 20 AMP**
- D 250 VOLT 30 AMP**

