

SCM, SCMPLUS & SCM1 Wiring Instructions

All three devices include two black wires and one green wire.
A surge protector works by shunting the voltage surge to ground.
A good ground is imperative. The National Electric Code (NEC)
maximum resistance at ground is 25 ohms.

240 Volt Wiring	120 Volt Wiring
Black to Hot	Black to Hot
Black to Hot	Black to Neutral
Green to Ground	Green to Ground



SEALED UNIT PARTS CO., INC.
2230 Landmark Place • Allenwood, N.J. 08720
(732)223-6644 • Fax (732)223-1617
www.supco.com • info@supco.com

SCM, SCMPLUS & SCM1 Wiring Instructions

All three devices include two black wires and one green wire.
A surge protector works by shunting the voltage surge to ground.
A good ground is imperative. The National Electric Code (NEC)
maximum resistance at ground is 25 ohms.

240 Volt Wiring	120 Volt Wiring
Black to Hot	Black to Hot
Black to Hot	Black to Neutral
Green to Ground	Green to Ground



SEALED UNIT PARTS CO., INC.
2230 Landmark Place • Allenwood, N.J. 08720
(732)223-6644 • Fax (732)223-1617
www.supco.com • info@supco.com

SCM, SCMPLUS & SCM1 Wiring Instructions

All three devices include two black wires and one green wire.
A surge protector works by shunting the voltage surge to ground.
A good ground is imperative. The National Electric Code (NEC)
maximum resistance at ground is 25 ohms.

240 Volt Wiring	120 Volt Wiring
Black to Hot	Black to Hot
Black to Hot	Black to Neutral
Green to Ground	Green to Ground



SEALED UNIT PARTS CO., INC.
2230 Landmark Place • Allenwood, N.J. 08720
(732)223-6644 • Fax (732)223-1617
www.supco.com • info@supco.com

SCM, SCMPLUS & SCM1 Wiring Instructions

All three devices include two black wires and one green wire.
A surge protector works by shunting the voltage surge to ground.
A good ground is imperative. The National Electric Code (NEC)
maximum resistance at ground is 25 ohms.

240 Volt Wiring	120 Volt Wiring
Black to Hot	Black to Hot
Black to Hot	Black to Neutral
Green to Ground	Green to Ground



SEALED UNIT PARTS CO., INC.
2230 Landmark Place • Allenwood, N.J. 08720
(732)223-6644 • Fax (732)223-1617
www.supco.com • info@supco.com

SCM, SCMPLUS & SCM1 Wiring Instructions

All three devices include two black wires and one green wire.
A surge protector works by shunting the voltage surge to ground.
A good ground is imperative. The National Electric Code (NEC)
maximum resistance at ground is 25 ohms.

240 Volt Wiring	120 Volt Wiring
Black to Hot	Black to Hot
Black to Hot	Black to Neutral
Green to Ground	Green to Ground



SEALED UNIT PARTS CO., INC.
2230 Landmark Place • Allenwood, N.J. 08720
(732)223-6644 • Fax (732)223-1617
www.supco.com • info@supco.com

SCM, SCMPLUS & SCM1 Wiring Instructions

All three devices include two black wires and one green wire.
A surge protector works by shunting the voltage surge to ground.
A good ground is imperative. The National Electric Code (NEC)
maximum resistance at ground is 25 ohms.

240 Volt Wiring	120 Volt Wiring
Black to Hot	Black to Hot
Black to Hot	Black to Neutral
Green to Ground	Green to Ground



SEALED UNIT PARTS CO., INC.
2230 Landmark Place • Allenwood, N.J. 08720
(732)223-6644 • Fax (732)223-1617
www.supco.com • info@supco.com

SCM, SCMPLUS & SCM1 Wiring Instructions

All three devices include two black wires and one green wire.
A surge protector works by shunting the voltage surge to ground.
A good ground is imperative. The National Electric Code (NEC)
maximum resistance at ground is 25 ohms.

240 Volt Wiring	120 Volt Wiring
Black to Hot	Black to Hot
Black to Hot	Black to Neutral
Green to Ground	Green to Ground



SEALED UNIT PARTS CO., INC.
2230 Landmark Place • Allenwood, N.J. 08720
(732)223-6644 • Fax (732)223-1617
www.supco.com • info@supco.com

SCM, SCMPLUS & SCM1 Wiring Instructions

All three devices include two black wires and one green wire.
A surge protector works by shunting the voltage surge to ground.
A good ground is imperative. The National Electric Code (NEC)
maximum resistance at ground is 25 ohms.

240 Volt Wiring	120 Volt Wiring
Black to Hot	Black to Hot
Black to Hot	Black to Neutral
Green to Ground	Green to Ground



SEALED UNIT PARTS CO., INC.
2230 Landmark Place • Allenwood, N.J. 08720
(732)223-6644 • Fax (732)223-1617
www.supco.com • info@supco.com